




Escovas tubulares ou escovilhões para limpeza de condutas - Rosca M12

Diâmetro		A		L		Aço	Aço	Aço Latonado	Nylon
Milímetros	Polegadas	Milímetros	Polegadas	Milímetros		0,35mm	0,50mm	0,30mm	
20	3/4	95	3-3/4	160	12	1900		1950	
25	1	95	3-3/4	160	12	1901		1951	
30	1-1/4	95	3-3/4	160	12	1902		1952	1977□□
35	1-3/8	95	3-3/4	160	12	1903		1953	
40	1-5/8	95	3-3/4	160	12	1904		1954	1979□□
45	1-3/4	95	3-3/4	160	12	1905		1955	
50	2	95	3-3/4	160	12	1906		1956	1981□□
55	2-1/8	95	3-3/4	160	12	1907		1957	
60	2-3/8	95	3-3/4	160	12	1908		1958	1983□□
65	2-5/8	95	3-3/4	160	12	1909		1959	
70	2-3/4	95	3-3/4	160	12	1910		1960	
75	3	95	3-3/4	160	12	1911		1961	
80	3-1/8	95	3-3/4	160	12	1912		1962	1987□□
85	3-3/8	95	3-3/4	160	12	1913		1963	
90	3-1/2	95	3-3/4	160	12	1914		1964	
95	3-3/4	95	3-3/4	160	12	1915		1965	
100	4	95	3-3/4	160	12	1916		1966	1991□□
120	4-3/4	95	3-3/4	160	12		1917□	1967	1992□□
130	5-1/8	95	3-3/4	160	6		1918	1968	
140	5-1/2	95	3-3/4	160	6		1919	1969	
150	6	95	3-3/4	160	6		1940		
160	6-1/4	95	3-3/4	160	6		1941		
180	7-1/8	95	3-3/4	160	6		1942		
200	8	95	3-3/4	160	6		1943□		
250	10	95	3-3/4	160	6		1944□		
300	12	95	3-3/4	160	6		1945□		

*) Ref 1917: Aço 0,45mm

**) Ref. 1977 : Nylon 0,40mm

*) Ref. 1943,1944,1945 : Aço 0,60mm

**) Ref 1979,1981,1983 : Nylon 0,60mm

**) Ref. 1987 : 0,80mm

**) Ref. 1991 : 1,00mm

**) Ref. 1992 : 1,20mm